

EXIMUS MODEL KB SERIES VERTICAL BANDSAWS

STANDARD EQUIPMENT & FEATURES:

- Infinitely variable cutting speed
- Adjustable blade guides top and bottom
- Blade tensioning via a hand wheel
- Robust steel frame with cast iron table
- Low voltage work lamp
- Table tilts $\pm 15^\circ$
- Blade welding with annealing device, blade shear & grinder
- Adjustable work light
- Integrated blade cleaning brush
- Manual with parts breakdown
- One saw blade and manuals

MODELS		UNIT	KB-30	KB-36	KB-45
Cutting capacity	throat depth	mm (in)	310 (12-3/8)	355 (14)	455 (17-15/16)
	max. work height	mm (in)	175 (6-7/8)	230 (9-1/16)	255 (10-1/16)
Table size		mm (in)	500x400 (19-1/2x15-1/4)	500x400 (19-1/2x15-1/4)	600x500 (23-1/2x19-1/2)
Table inclination(4ways)			15°	15°	15°
Saw blade length		mm (in)	2520 (99-1/4)	2840 (111-13/16)	3490 (137-3/8)
Saw blade width		mm	3-16	3-16	3-16
Saw blade speeds		mm(fpm)	20-90 (65-295)	20-90 (65-295)	25-115 (85-375)
Butt welder capacity		mm (in)	2.4KVA, 3-16mm (1/8-5/8)	2.4KVA, 3-16mm (1/8-5/8)	2.4KVA, 3-16mm (1/8-5/8)
Drive motor		HP (KW)	1/2HP (0.4)	1HP (0.75)	1HP (0.75)
Net weight (approx.)		Kgs (Ibs)	225 (496)	250 (551)	300 (660)
Gross weight(appros.)		Kgs (Ibs)	285 (628)	310 (683)	370 (814)
Measurement (LxWxH)		mm (in)	920x550x1680 (36-3/16x 21-11/16x 66-3/16)	940x560x1850 (37-3/16x 22x72-13/16)	1110x660x2020 (43-11/16x 26x79-1/4)

STANDARD EQUIPMENT:

- Blade cleaning brush
- Rip fence for straight, repeated cutting
- Mitre protractor
- Groove table



